

AH  
Concl'd

A second gap is formed between the auxiliary electrode and the second sustaining electrode. The second gap is smaller than the first gap.--

5 In the claims:

Please amend claims 1, 7, 9-10, 13, and 16-20 as follows:

10 1. (Once amended) An electrode structure of a plasma display panel (PDP), the electrode structure formed on a front substrate of the PDP, and comprising:  
a first sustaining electrode and a second sustaining electrode set on the surface of the front substrate, and a first gap existing between the first and second sustaining electrodes; and

15 a first auxiliary electrode electrically connected to the first sustaining electrode, the first auxiliary electrode comprising a first part and a second part adjacent to the first part, the first part formed in the first gap, and the second part located above the first sustaining electrode;

20 wherein a second gap existing between the first part of the first auxiliary electrode and the second sustaining electrode is used as a discharge gap of the electrode structure of the PDP, and the width of the  
25 second gap is smaller than the width of the first gap.

AB

30 7. (Once amended) The structure of claim 21 wherein the second sustaining electrode comprises a third side not contiguous to the end of the first sustaining electrode, and the electrode structure also comprises a second auxiliary electrode approaching to the third

AB  
concl'd

side of the second sustaining electrode.

A7

9. (Once amended) An electrode structure of a plasma display panel (PDP), the electrode structure formed on a front substrate of the PDP, and comprising:

5 a first sustaining electrode and a second sustaining electrode formed on the front substrate, and a first gap existing between the first and second sustaining electrodes; and

10 a first auxiliary electrode formed on the surface of the substrate in the first gap;

wherein a second gap existing between the first auxiliary electrode and the second sustaining electrode is used as a discharge gap of the electrode structure of the PDP, and the width of the second gap is smaller than the width of the first gap.

10. (Once amended) The structure of claim 9 wherein the first sustaining electrode comprises a first side approaching to the second sustaining electrode and a second side not contiguous to the end of the second sustaining electrode, the first auxiliary electrode comprises a first part and a second part, the first part is formed in the first gap, and the second part is located approaching to the second side of the first sustaining electrode.

A8

13. (Once amended) The structure of claim 9 wherein the second sustaining electrode comprises a third side not contiguous to the end of the first sustaining electrode, and the electrode structure further comprises a second auxiliary electrode approaching to

AS  
concl'd

the third side of the second sustaining electrode.

A9

5 16. (Once amended) The structure of claim 9 wherein  
the first sustaining electrode comprises a first side  
approaching to the second sustaining electrode and a  
second side not contiguous to the end of the second  
sustaining electrode, and the first auxiliary electrode  
is formed on the surface of the front substrate and  
adjacent to the first side of the first sustaining  
10 electrode.

17. (Once amended) An electrode structure of a plasma  
display panel (PDP), the electrode structure formed  
on a front substrate of the PDP, and comprising:

15 a first sustaining electrode formed on the surface  
of the front substrate;

a first auxiliary electrode formed on the surface  
of the front substrate and parallel to the first  
sustaining electrode, a first gap existing between the  
20 first sustaining electrode and the first auxiliary  
electrode; and

a second auxiliary electrode formed on the surface  
of the front substrate and parallel to the first  
sustaining electrode, a second gap existing between  
25 the first sustaining electrode and the second auxiliary  
electrode and being used as a discharge gap of the  
electrode structure of the PDP, and the width of the  
second gap being smaller than the width of the first  
gap.

30

18. (Once amended) The structure of claim 17 wherein  
the first sustaining electrode comprises a first side

Q

A9  
concl'd

approaching to the second auxiliary electrode and a second side not contiguous to the end of the second auxiliary electrode, and the electrode structure comprises a third auxiliary electrode adjacent to the second side of the first sustaining electrode.

19. (Once amended) The structure of claim 18 wherein a connecting electrode is formed between the first and the second auxiliary electrodes, and the connecting electrode is formed on the surface of the front substrate and perpendicular to the first auxiliary electrode.

20. (Once amended) The structure of claim 18, further comprising a fourth auxiliary electrode formed on the surface of the front substrate, the fourth auxiliary electrode formed between the first and the second auxiliary electrodes, a third gap existing between the fourth auxiliary electrode and the first sustaining electrode, and the width of the third gap is smaller than the width of the first gap.

[ Please add claim 21 as follows: ]

A10

21. (New) The structure of claim 1 wherein the first sustaining electrode has a first side approaching to the second sustaining electrode and a second side not contiguous to the end of the second sustaining electrode.

30

a